

# CERTIFICATE

Issued to:

Applicant:

**Boltek Plastik Ve Elektrik Kontrol Cihazları San. Ve Tic. Ltd. Şti.**

**Susuz Kinik Koyu Susuz Kinik OSB Mevkii 6.**

**Cadde No:8**

**14030 Bolu, Turkey**

Licensee:

**Boltek Plastik Ve Elektrik Kontrol Cihazları San. Ve Tic. Ltd. Şti.**

**Susuz Kinik Koyu Susuz Kinik OSB Mevkii 6.**

**Cadde No:8**

**14030 Bolu, Turkey**

Product : Rocker switches  
Trade name(s) : BOLTEK  
Type(s)/model(s) : DB Series, DF Series and DS Series

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard(s) EN 61058-1-1:2016 and EN IEC 61058-1:2018
- an inspection of the factory location according to CENELEC Operational Document CIG 021
- a DEKRA certification agreement with the number 6059640


DEKRA hereby grants the right to use the KEMA-KEUR certification mark.

The KEMA-KEUR certification mark may be applied to the product as specified in this certificate for the duration and under the conditions of the KEMA-KEUR certification agreement.

This certificate is issued on 7 May 2021 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 71-118674

DEKRA Certification B.V.



B.T.M. Holtus  
Managing Director



R Zhou  
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE  
DUTCH ACCREDITATION  
COUNCIL



**SPECIFICATION OF THE CERTIFIED PRODUCT****Product data**

Product	: Rocker switches
Trade name(s)	: BOLTEK
Type(s)/model(s)	: DB Series, DF Series and DS Series
Type reference	: common type (C.T.)
Type of switch	: incorporated
Rated voltage	: 250 V~
Rated current	: 16(4) A 10(2) A 10 A
Circuit to be controlled	: substantially resistive resistive and/or motor
Temperature limit	: T125/55 T85/55
Contact opening	: full disconnection
Class	: for class II appliances
Degree of protection	: IP40
Degree of pollution	: PD2 for both micro and macro
Insulating material	: tracking resistant (250 V)
Resistance to glow wire test	: 850 °C
Rated impulse withstand voltage	: 2500 V
Material group	: IIIa
Terminals	: tab terminals (6,3 x 0,8 mm)
Markings	: are moulded on the body

**Product data – type DB Series**

Pattern no.	: 2 x single pole
Circuit code	: 2 x 1.2

**Product data – type DF Series**

Pattern no.	: single pole
Circuit code	: 1.2

**Product data – type DS Series**

Pattern no.	: double pole
Circuit code	: 1.3

**TESTS****Test requirements**

EN 61058-1-1:2016  
EN IEC 61058-1:2018

**Test result**

The test results are laid down in DEKRA test file 225557300.

**Conclusion**

The examination proved that all requirements were met.

**Factory location**

Boltek Plastik Ve Elektrik Kontrol Cihazları San. Ve Tic. Ltd. Şti.  
Susuz Kinik Koyu Susuz Kinik OSB Mevkii 6. Cadde No:8  
14030 Bolu, Turkey